



APC Smart-UPS On-Line, 2200VA, Tower, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

SRT2200XLI

Overview

Presentation High density, double-conversion on-line power protection with scalable re				
Lead time	Usually in Stock			
Main				
Main Input Voltage	230 V			
Product or component type	Uninterruptible power supply (UPS)			
Other Input Voltage	220 V 240 V			
Main Output Voltage	230 V			
Other Output Voltage	220 V 240 V			
Rated power in W	1980 W			
rated power in VA	2200 VA			
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P			
output connection type	8 IEC 60320 C13 2 IEC Jumpers 2 IEC 60320 C19			
Cable length	2.4 m			
Number of cables	1			
Provided equipment	CD with software Country-specific detachable power cord Documentation CD Installation guide Removable support feet USB cable			

Batteries & Runtime

Range of product

Run Time	View Runtime Graph ☐		
Efficiency	View Efficiency Graph ☐		
Battery type	Lead-acid battery		
Battery voltage	72 V		
Extended runtime	1		
Number of battery filled slots	1		

Warranty card

Smart-UPS On-Line

List Price displayed is VAT EXCLUSIVE.

Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	35 year(s)
Replacement battery	APCRBC141 ☐
Battery charger power	122 W rated

General

Number of power module	1400
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	High density
Redundant	No
UPS type	Double conversion online

Physical

•				
Colour	Black			
Height	43.2 cm			
Width	8.5 cm			
Depth	58.4 cm			
Net weight	25 kg			
Mounting location	Front			
Mounting preference	Lower			
Mounting mode	Rack-mounted with kit			
Two post mountable	0			
USB compatible	Yes			
Mounting position	Vertical			

Input

Input voltage limits	100275 V adjustable (half load)
Network frequency	4070 Hz auto-sensing

Output

Bypass type	Internal bypass (automatic and manual)	
Crest factor	3:1	
Harmonic distortion	Less than 2 %	
Maximum configurable power in VA	2200 VA	
Maximum configurable power in W	1980 W	
Wave type	Sine wave	
Output frequency	50/60 Hz +/- 3 Hz sync to mains	
Additional information	Configurable for 220 : 230 or 240 nominal output voltage	

Conformance

Product certifications	CE	
	EAC	
	RCM	
	VDE	
	UK PSTI	
Marking	CE Mark	
Standards	EN/IEC 62040-1:2019/A11:2021	
	EN/IEC 62040-2:2006/AC:2006	
	EN/IEC 62040-2:2018	

Environmental

Acoustic level	55 dBA	
Heat dissipation	703 Btu/h	
Operating altitude	010000 ft	
Ambient air temperature for operation	040 °C	
Ambient air temperature for storage	-1545 °C	
Storage altitude	015240 m	
IP degree of protection	IP20	
Relative humidity	095 % non-condensing	
Storage Relative Humidity	095 % non-condensing	

Communications & Management

Emergency power off	Yes
Free slots	1
Alarm	Audible and visible alarms : prioritized by severity

Surge Protection and Filtering

Surge energy rate 340 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.600 cm
Package 1 Width	59.900 cm
Package 1 Length	81.000 cm
Package 1 Weight	30.840 kg
Unit Type of Package 2	P12
Number of Units in Package 2	2
Package 2 Height	55.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	74.000 kg

Contractual warranty

۱۸	lai	rr	٦n	t٠

3 years repair or replace (excluding battery) and 2 years for battery



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	3634
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Not compliant
SCIP Number	4282bd22-a353-4f82-bb5c-97bbd7f1d1e9
REACh Regulation	REACh Declaration
Energy Efficiency Optimized	Energy efficient product

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product data sheet

SRT2200XLI

Image of product / Alternate images

Alternative





